



# CANYCOM USA

**CANYCOM**

Forging cross-cultural relationships  
through developing "need-specific" products.

[www.canycomsales.com](http://www.canycomsales.com)

# S25APD

## Heavy-duty Compact Carrier with Pivoting Deck

- ⦿ 90° Dump Angle
- ⦿ Max. Payload 5510lbs.
- ⦿ 46 HP



Instrument Panel



Air Cleaner



Quick Pivoting Seat



Engine Compartment



Heavy-duty Undercarriage

KUBOTA V2203 Diesel Engine



# S160PD

## Medium-duty Carrier

- ⦿ Width 44"
- ⦿ Max. Payload 3530lbs.
- ⦿ 20.5 HP



# HYDROSTATIC

# Concrete Buggy SC75

# UTILITY



## BFP602M



Control Panel



Model		S25APD	S160PD	S100FD	S100PD	SC75	BP416MB/MF	BFP602MB/
Max. Loading Capacity	lbs.	5510	3530	2210	2210	1655	600	1000
Overall Length x Width x Height	in.	147 x 66 x 94	112 x 44 x 94	103 x 39 x 54	104 x 39 x 51	106 x 35 x 58	65 x 25 x 39	77 x 31 x 4
Machine Weight	lbs.	5176	3020	1839	1982	141	319	474
Bed Inner Length x Width x Height	in.	86 x 52 x 20	58 x 40 x 22	53 x 36 x 20	53 x 36 x 20	51 x 30 x 21	38 x 21 x 17	48 x 29 x 8
Bed Floor Height	in.	36	25	22	25	18		17
Engine		Kubota	Kubota	Kubota	Kubota	Robin	Mitsubishi	Mitsubishi
Engine Type		V2203	D1105	D722	D722	EH65	GM132	GM182
Max. Output	HP/rpm	46.0/2800	20.5/2400	15.0/3000	15.0/3000	18.5/3300	4.0/1800	6.0/2000
Engine Displacement	cc		1123	719	719	653	126	181
Cylinder No.			3	3	3	2		
Fuel Tank Capacity	gal.		6	4	4	5	1	2
Transmission		2 speed Hydrastatic	Hydrastatic	Hydrastatic	Hydrastatic	Hydrastatic	Manual	Manual
Number of gears / Forward		-	-	-	-	-	2	3
Number of gears / Reverse		-	-	-	-	-	2	2
Max. Speed/ Forward	mph	7	7	6	6	5	5	5
Max. Speed/ Reverse	mph		4			4	4	3
Min. Ground Clearance	in.	12	6	6	6	5	4	4
Dumping system		Hydraulic	Hydraulic	Hydraulic	Hydraulic	Hydraulic	Manual	Manual
Dumping Direction		Pivoting	Pivoting	1-way Dump	Pivoting	1-way Dump	1-way Dump	1-way Dump
Rubber Track width			11	9	9	8	7	7
Tread	in.	49	33	30	30	28	18	22
Track Ground Contact		78	47	46	46	38		
Gradeability	degree	25(unloaded)	25(unloaded)	25(unloaded)	25(unloaded)	25(unloaded)	25(unloaded)	25(unloaded)
Counter Rotating Track		Yes	Yes	Yes	Yes	Yes	No	No
Swing lower Rollers		Yes	Yes	Yes	Yes	Yes	Yes	No
Tipping Angle	degree	85	90	90	90	90	55	60
Tipping Height	in.		30	23	23	11		
Generator		-	-	-	-	-	-	-
DC Output		-	-	-	-	-	-	-

# RUBBER TRACK

## BP416MB/MF



BP416MB



BP416MF

B/MT

## EG60

Carrier with Generator



BFP602MB



BFP602MT



EG60	CM230
560	1000
57 x 26 x 40	89 x 45 x 75
463	1080
38 x 21 x 17	-
15	-
Robin	Kawasaki
EX17D	FH680V
6.0/4000	23/3600
	675
	2
2	8
Manual	Hydrastatic
2	2
2	2
5	6
4	-
	5
Manual	-
3-way Dump	-
7	-
18	F:33.1 / R:36.7
28	-
5(unloaded)	20
No	-
Yes	-
55	-
	-
1.4kva/60Hz	-
12V-8.3A	-

## CM230

Ride-on Brush Cutter



Foot operated F/R Drive



Blade



Spinning Blade



Ⓢ Battery Compartment



Ⓢ Control Panel



Ⓢ Fuel Tank



Ⓢ Engine Compartment



Ⓢ Heavy-duty Undercarriage



## S100FD

Light-duty Carrier with  
One-way Dump Flat Deck

- Ⓢ Width 39"
- Ⓢ 70° Dump Angle
- Ⓢ Max. Payload 2210lbs.
- Ⓢ 15 HP



## S100PD

Light-duty Carrier with  
180° Pivoting Dump Deck

- Ⓢ Width 39"
- Ⓢ 90° Dump Angle
- Ⓢ Max. Payload 2210lbs.
- Ⓢ 15 HP



# RUBBER TRACK



Above : CM230 Ride-on Brush Cutter



# EJ10

## Electric Utility Equipment

- Ⓢ Towing-type Cart
- Ⓢ Max. Payload 220lbs.
- Ⓢ Environment-friendly!



\* CANYCOM reserves the right to change specifications without notice.

**CANYCOM**

### CANYCOM USA, INC.

500 108th Ave. NE, Suite 955, Bellevue, WA 98004

Tel: 425-450-0381 Fax: 425-450-0384

E-mail: [info@canycomsales.com](mailto:info@canycomsales.com)

[www.canycomsales.com](http://www.canycomsales.com)